

C45

The powerful hydraulic feed system of this diesel powered chipper makes it easy to process any material. Its wide feed opening pulls bushy and twisted branches with forks into the machine without effort. Activate the feed roller with the control bar and the rest is taken care of by the electronic automatic sensor feed system.



Application



Commercial

Specifications



Feature



Disc Brakes

Option



Bottom Safety Bar

C65

Widely considered to be the best in its class, this powerful, lightweight, manoeuvrable hydraulic feed chipper boasts extraordinary capacity to weight ratio. This feature is accentuated by its wide feed opening – often described as a 'small in size but big in capacity' chipper, all achieved through clever design and manufacturing.



Application



Commercial

Specifications



Option



Hydraulic Winch



Lift & Crush



Bottom Safety Bar

COMMERCIAL



	C25	C27	C45	C65	C65RX
Max. chipping capacity	160mm (6")	160mm (6")	178mm (7")	254mm (10")	254mm (10")
Engine	Honda GX690	Honda GX800	Deutz F3L 2011	Deutz F4L 2011	Deutz F4L 2011
Max Power	25HP	28HP	48HP	64HP	64HP
Fuel type	Petrol	Petrol	Diesel	Diesel	Diesel
Fuel tank size	33L	33L	45L	70L	70L
Hydraulic tank size	23L	23L	24L	50L	92L
Starting system	Electric				
Inlet opening size	330 x 178mm	330 x 178mm	330 x 178mm	458 x 254mm	458 x 254mm
Qty of knives	2, reversible	2, reversible	2, reversible	4, reversible	4, reversible
Knife size	200 x 116 x 16mm	200 x 116 x 16mm	200 x 116 x 16mm	200 x 116 x 16mm	200 x 116 x 16mm
Knife material	A8 modified tool steel				
Cutting disk dimensions	650 x 20mm	650 x 20mm	650 x 25mm	800 x 40mm	800 x 40mm
Cutting disk weight	81kg	81kg	94kg	181kg	181kg
Cutting disk speed	1800RPM	1800RPM	1800RPM	1700RPM	1700RPM
Beltdrive	3 x B Section	3 x B Section	3 x SPB Section	4 x SPB Section	4 x SPB Section
Feedroller diameter	220mm	220mm	220mm	300mm	300mm
Wheels	13" rim	13" rim (low profile)	13" rim	14" rim	Rubber tracks
Disk brakes	No	No	Yes	Yes	n/a
Dimensions (l x w x h)	3160 x 1580 x 2165mm (w. Bump Bar 3270 lmm)	3160 x 1650 x 2180mm (w. Bump Bar 3270 lmm)	3676 x 1618 x 2186mm 3786 x 1618 x 2186mm (w.Bump Bar)	4034 x 1800 x 2360mm 4164 x 1800 x 2360mm (w.Winch) 4144 x 1800 x 2360mm (w.Bump Bar)	3130 x 1430 x 2325mm 3260 x 1430 x 2325mm (w.Winch) 3240 x 1430 x 2325mm (w.Bump Bar)
Weight (depending on options)	780-885kg	925-1030kg	1290-1340kg	1740-1950kg	2030-2190kg
Outlet chute height	2165mm	2180mm	2010-2190mm	2140 - 2360mm	2110 - 2325mm
Outlet chute type	360° swivel		360° swivel, height adjustable		